







Our Products

Arone	Applications	Products
Areas	Applications	Products Defravilles 445 DTC
1) Impact area	One shot impact plate in precast mix	Refravibre 445 RTC
	Long life impact plate in high alumina precast mixes	Refravibre 870, S220
	Precast skimmers in precast mix	Refravibre 445 RTC
	Castable mixes for sealing impact plate	Beton 86 B/P, 96 A
	Plastic mortar for sealing impact plate	PR 110 CA, 116 CA
	Cement for sticking impact plate and skimmer	Refracol 6,6CC
2) Tundish cover	Castable mixes for working lining	Refravibre 465 RTC
	Half insulating castable mix for wear lining	Beton 770
	Cement for sticking insulating lining	Refracol 12 A
	Precast cover without metal shell	In FibroCeram RXO
3) Sidewall and bottom	Castable mixes for permanent lining	Refravibre 465 RTC
	Repairing plastic mortar	PR 110 CA, PR 116 CA
	Cements for filling cracks in permanent lining	Refracol 6, 306 T1 P8
	Cement for sticking insulating lining	Refracol 12 A
	Bi-component repairing mix	Refravibre H882, H882T
	Blocking mix for precast cuve	Caloref TSF, Refram 545H
4) Submerged nozzle	Air setting mortar for sealing nozzle in the well block	Refracol 6 CC
	Hot setting mortar for sealing nozzle	Refracol 620, 620 A
	Mastic for protecting down part of nozzle	Refracol 25 Bis
	Ramming mix for sealing well block	Refracol 33 A4, 37 A4
	Precast well block	inRefravibre 445 RTC
	Glue for stick insulation parts around nozzle	Refracol 12 A
5) Calibred nozzle	Ramming mix around calibred nozzle	Refracol 38 A4, 37 A4
	Air setting cement under calibred nozzle	Refracol 3, 13
	Ramming mix for form ther poring cone	Mixomag 785 H, 192
6) Slide gate system	Air setting mortar for sealing nozzle in the well block	Refracol 6 CC
	Hot setting mortar for sealing nozzle	Refracol 620, 620 A
	Precast well block	In Refravibre 445 RTC
	Ramming mix around well block	Refracol 33 A4, 37 A4
	Ramming mix for sealing nozzle without well block	Refracol 38 A4, 37 A4

REFRACOL DUPONT et Cie

35 rue de la Gare - 59770 MARLY - France W : www.refracol.com – M : contact@refracol.com – T : +33 (0)3 27 46 37 76

